



PONTRILAS SAWMILLS LTD.

Construction Products Regulation

DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type:

GS/C14, GS/C16, SS/C18, SS/C22, & SS/C24 strength graded softwood (as per delivery note)

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

VSG Softwood

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Structural timber to be used for studs, joists, purlins, rafters and beams

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

Pontrilas Sawmills Ltd.

Pontrilas

Near Hereford

HR2 0BE

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 14081-1:2005 + A1:2011

CATG 1245 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued the certificate of constancy of performance.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Strength grade of Timber	GS/C14, GS/C16, SS/C18, SS/C22, & SS/C24 As per delivery note	
Reaction to Fire	D-s2, d0	
Release of dangerous substances	NPD	
Natural durability (not treated)	Class 4	
Durability for timber if treated	Use Class 3	EN 14081:2005 + A1:2011
Type of Treatment & Preservative if treated	Tanalith E 8000	
Penetration Class if treated	NP3	
Retention Values if treated	8.5 kg/m3	
Target Biological Agents if treated	Insect and fungi	

Specific technical documentation:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

B. Pugh
Operations Director
28/2/14